



GLEDDL 20W

DOWNLIGHT SPECIFICATION SHEET



▼ CERTS



RoHS



▼ DIMENSIONS




6" FIXTURE

Diameter:
7.48 in (190 mm)

Height:
7.48 in (190 mm)

▼ PHOTOMETRICS



40°
BEAM ANGLE

▶ OPTICAL SPECS

| | |
|----------------|-----------------------|
| Lumen Efficacy | Up to 80 Lm/W |
| Lumen Output | 1,600 Lm |
| CCT | 27K / 30K / 40K / 50K |
| CRI | ≥ 83 Ra |
| Beam Angle | 40° |

▶ ELECTRICAL SPECS

| | |
|--------------------|--------------------|
| System Power Usage | 20W |
| Input Voltage | AC 100 - 277 Volts |
| Power Frequency | 50/60 Hz |
| Power Factor | ≥ 0.9 |
| Efficiency | ≥ 85% |
| Output Current | 480mA |

▶ OTHER DETAILS

| | |
|-----------------------|--------------------------------------|
| Ingress Protection | IP20 |
| Fixture Material | Aluminum Alloy |
| Lifespan | ≥ 36,000 Hours |
| Storage Temperature | -4° ~ 149°F (-20° ~ 65°C) |
| Operating Temperature | -4° ~ 113°F (-20° ~ 45°C) |
| Product Dimensions | ø 7.48 x 7.48 in (ø 190 x 190 mm) |

