



GLEDDL 25W

DOWNLIGHT SPECIFICATION SHEET



▼ CERTS



RoHS



▼ DIMENSIONS




6" FIXTURE

Diameter:
7.48 in (190 mm)

Height:
7.48 in (190 mm)

▼ PHOTOMETRICS



40°
BEAM ANGLE

▶ OPTICAL SPECS

| | |
|----------------|-----------------------|
| Lumen Efficacy | Up to 76 Lm/W |
| Lumen Output | 1,900 Lm |
| CCT | 27K / 30K / 40K / 50K |
| CRI | ≥ 83 Ra |
| Beam Angle | 40° |

▶ ELECTRICAL SPECS

| | |
|--------------------|--------------------|
| System Power Usage | 25W |
| Input Voltage | AC 100 - 277 Volts |
| Power Frequency | 50/60 Hz |
| Power Factor | ≥ 0.9 |
| Efficiency | ≥ 85% |
| Output Current | 600mA |

▶ OTHER DETAILS

| | |
|-----------------------|--------------------------------------|
| Ingress Protection | IP20 |
| Fixture Material | Aluminum Alloy |
| Lifespan | ≥ 36,000 Hours |
| Storage Temperature | -4° ~ 149°F (-20° ~ 65°C) |
| Operating Temperature | -4° ~ 113°F (-20° ~ 45°C) |
| Product Dimensions | ø 7.48 x 7.48 in (ø 190 x 190 mm) |

After choosing options to create the perfect controlled fixture for your space, this chart will help you create the correct SKU necessary to order.

DOWNLIGHT

| PRODUCT | WATTAGE | ^A CCT | ^B FIXTURE LENGTH |
|---------|---------|-----------------------|-----------------------------|
| GLEDDL | 15W | 27K / 30K / 40K / 50K | 4 |
| GLEDDL | 20W | 27K / 30K / 40K / 50K | 4 / 6 |
| GLEDDL | 25W | 27K / 30K / 40K / 50K | 6 / 8 |
| GLEDDL | 30W | 27K / 30K / 40K / 50K | 6 |
| GLEDDL | 35W | 27K / 30K / 40K / 50K | 8 |
| GLEDDL | 42W | 27K / 30K / 40K / 50K | 8 / 10 |
| GLEDDL | 50W | 27K / 30K / 40K / 50K | 10 |

Create your SKU:

GLEDDL

PRODUCT

WATTAGE

CCT

LENGTH (FIXED)

Accessory SKUs if applicable (separate by comma)

Fixture Quantity

SKU CREATOR GUIDELINES

- Options in chart separated by slash (/)
- Choose one option per column.
- All characters must **always** utilize capitalization. No special characters (/,&,#,etc.) will be permitted.
- White space in between columns indicates single space in SKU.

SKU CREATOR CATEGORY KEY

CCT - COLOR TEMP.

- ^A **27K** - 2,700 Kelvin
- 30K** - 3,000 Kelvin
- 40K** - 4,000 Kelvin
- 50K** - 5,000 Kelvin

FIXTURE LENGTH

- ^B **4** - 4 inch diameter
- 6** - 6 inch diameter
- 8** - 8 inch diameter
- 10** - 10 inch diameter

NOTES
