



GLEDDL 35W

DOWNLIGHT SPECIFICATION SHEET



▼ CERTS



RoHS




▼ DIMENSIONS



Diameter:
7.48 in (190 mm)

Height:
8.07 in (205 mm)

▼ PHOTOMETRICS



▶ OPTICAL SPECS

Lumen Efficacy	Up to 80 Lm/W
Lumen Output	2,800 Lm
CCT	27K / 30K / 40K / 50K
CRI	≥ 83 Ra
Beam Angle	40°

▶ ELECTRICAL SPECS

System Power Usage	35W
Input Voltage	AC 100 - 277 Volts
Power Frequency	50/60 Hz
Power Factor	≥ 0.9
Efficiency	≥ 85%
Output Current	820mA

▶ OTHER DETAILS

Ingress Protection	IP20
Fixture Material	Aluminum Alloy
Lifespan	≥ 36,000 Hours
Storage Temperature	-4° ~ 149°F (-20° ~ 65°C)
Operating Temperature	-4° ~ 113°F (-20° ~ 45°C)
Product Dimensions	ø 7.48 x 8.07 in (ø 190 x 205 mm)

After choosing options to create the perfect controlled fixture for your space, this chart will help you create the correct SKU necessary to order.

DOWNLIGHT

PRODUCT	WATTAGE	^A CCT	^B FIXTURE LENGTH
GLEDDL	15W	27K / 30K / 40K / 50K	4
GLEDDL	20W	27K / 30K / 40K / 50K	4 / 6
GLEDDL	25W	27K / 30K / 40K / 50K	6 / 8
GLEDDL	30W	27K / 30K / 40K / 50K	6
GLEDDL	35W	27K / 30K / 40K / 50K	8
GLEDDL	42W	27K / 30K / 40K / 50K	8 / 10
GLEDDL	50W	27K / 30K / 40K / 50K	10

Create your SKU:

GLEDDL

PRODUCT

WATTAGE

CCT

LENGTH (FIXED)

Accessory SKUs if applicable (separate by comma)

Fixture Quantity

SKU CREATOR GUIDELINES

- Options in chart separated by slash (/)
- Choose one option per column.
- All characters must **always** utilize capitalization. No special characters (/,&,#,etc.) will be permitted.
- White space in between columns indicates single space in SKU.

SKU CREATOR CATEGORY KEY

CCT - COLOR TEMP.

^A
27K - 2,700 Kelvin
30K - 3,000 Kelvin
40K - 4,000 Kelvin
50K - 5,000 Kelvin

FIXTURE LENGTH

^B
4 - 4 inch diameter
6 - 6 inch diameter
8 - 8 inch diameter
10 - 10 inch diameter

NOTES
