



GLEDSR 65W S

STRIP LIGHT SURFACE MOUNT SPECIFICATION SHEET



▼ CERTS




RoHS



▼ DIMENSIONS

8' FIXTURE




Length: 96 in (2438.2 mm)

Width: 3.56 in (90.5 mm)

Height: 3.35 in (85.2 mm)

▼ PHOTOMETRICS



120°
Frosted Cover

▶ OPTICAL SPECS

| | |
|-----------------|--------------------|
| System Efficacy | Up to 132 Lm/W |
| Lumen Output | Up to 8,580 Lumens |
| CCT | 35K / 40K / 50K |
| CRI | > 80 Ra |
| Beam Angle | 120° |

▶ ELECTRICAL SPECS

| | |
|---------------------------|--------------------|
| Input Voltage | AC 100 - 277 Volts |
| Power Frequency | 50 / 60 Hz |
| Power Factor | > 0.90 |
| Efficiency | > 85% |
| Total Harmonic Distortion | < 10% |
| Dimming Function | 0 - 10V |

▶ OTHER DETAILS

| | |
|-----------------------|--|
| System Power Usage | 65W |
| Ingress Protection | IP20 |
| Luminaire Net Weight | 8.6 Kg |
| Lifespan | ≥ 100,000 Hours |
| Operating Temperature | -4° to 122°F (-20° to 50°C) |
| Product Dimensions | 96 x 3.56 x 3.35 in (2438.2 x 90.5 x 85.2 mm) |

▶ CONTROLS & ACCESSORIES

| | |
|----------------------|-------------------------|
| Intelligent Control | Dimming / Motion Sensor |
| Back-up Power Supply | 5W / 8W / 16W / 25W |

*Consult your GEL sales representative or the DLC QPL for specific model certifications.

After choosing options to create the perfect controlled fixture for your space, this chart will help you create the correct SKU necessary to order.

STRIP LIGHT SURFACE MOUNT

| PRODUCT | WATTAGE | A CCT | B FIXTURE LENGTH | C SURFACE MOUNT |
|---------|---------|-----------------|------------------|-----------------|
| GLEDSR | 23W | 35K / 40K / 50K | 4 | S |
| GLEDSR | 32W | 35K / 40K / 50K | 4 | S |
| GLEDSR | 35W | 35K / 40K / 50K | 4 | S |
| GLEDSR | 46W | 35K / 40K / 50K | 8 | S |
| GLEDSR | 65W | 35K / 40K / 50K | 8 | S |

Create your SKU:

GLEDSR

| PRODUCT | WATTAGE | CCT | LENGTH | OPTIONS | FIXTURE QUANTITY |
|---------|---------|-----|--------|---------|------------------|
|---------|---------|-----|--------|---------|------------------|

Accessory SKUs if applicable (separate by comma)

ACCESSORY SKUS

Order accessories as separate part number from your Fixture SKU.
Learn more about these options on the Accessories Page.

► MOTION CONTROL

| SKU | DESCRIPTION |
|-----------------------|--|
| GLEDSRA Motion Sensor | LED Strip Light Retrofit Kit Motion Sensor |
| GLEDSRA Programmer | Handheld Wireless Programmer |

► BACK-UP POWER SUPPLY

| SKU | DESCRIPTION |
|---------------------|---|
| GLEDSRA BACK UP 5W | Emergency Back Up Power Supply 5w Output |
| GLEDSRA BACK UP 8W | Emergency Back Up Power Supply 8w Output |
| GLEDSRA BACK UP 16W | Emergency Back Up Power Supply 16w Output |
| GLEDSRA BACK UP 25W | Emergency Back Up Power Supply 25w Output |

SKU CREATOR GUIDELINES

- Options in chart separated by slash (/)
- Choose one option per column.
- All characters must **always** utilize capitalization. No special characters (/ , & , #, etc.) will be permitted.
- White space in between columns indicates single space in SKU.

SKU CREATOR CATEGORY KEY

To select standard fixture - leave **OPTIONS** column blank.

| A CCT - COLOR TEMP. | B FIXTURE LENGTH | C SURFACE OPTIONS |
|---|--------------------------------------|--------------------------|
| 35K - 3,000 Kelvin 40K - 4,000 Kelvin 50K - 5,000 Kelvin | 4 - 4 ft. 8 - 8 ft. | S - Surface Mount |