

# GLEDLL-80W

## SPECIFICATIONS



CB CE FC RoHS



### Features:

- Direct Replacement for Tube Fixtures
- Multiple Mounting Options
- 0-10 Volt Dimming
- Linkable Option
- 120° Wide Beam Angle
- 5-year warranty


### Dimensions:

Length (A): 47.24in (1200mm) Height (B): 3.35in (85mm) Width (C): 4.29in (109mm)




### Photometrics:

Clear Cover



Frosted Cover



### PART NUMBER KEY:

[XX = Finish Options, L = Linkable Installation, D = Dimming, M = Motion Controls with Dimming, LD = Linkable Dimming, LM = Linkable Motion with Dimming]

GLEDLL	-	80W	-	XX	-	CCT	-	Options
				CC		3K		L
				FC		4K		D
						5K		M
								LD
								LM

Example: GLEDLL-80W-CC-3K-LM

### Optical Details: (Clear Cover)

Lumen Efficacy	Up to 142 Lm/W (CCT = 5000K)
Lumen Output	11,360 Lm (CCT = 5000K)
CCT	3000K, 4000K, 5000K, 6000K
CRI	> 80 Ra
Beam Angle	120°

### Optical Details: (Frosted Cover)

Lumen Efficacy	Up to 132 Lm/W (CCT = 5000K)
Lumen Output	10,560 Lm (CCT = 5000K)
CCT	3000K, 4000K, 5000K, 6000K
CRI	> 80 Ra
Beam Angle	120°

### Electrical Details:

System Power Usage	81.63 Watts
Input Voltage	AC 100-277 Volts
Power Frequency	50/60 Hz
Efficiency	> 90%
Power Factor	> 0.90

### Other Details:

Ingress Protection	IP65
Storage Temperature	-40°-185°F (-40-85°C)
Operating Temperature	-4°-113°F (-20-45°C)
Product Dimensions	47.24 x 3.35 x 4.29in (1200 x 85 x 109mm)

### Accessories:

All accessories must be ordered as a separate item.



**Starter Kit**  
GLEDLL-Starter Kit



**Linking Clip**  
GLEDLL-Linking Clip



**Programmer**  
GLEDLL-Programmer



**Mounting Cable (1.5 meters)**  
GLEDLL-Mounting Cable 1.5m



**Motion Sensor Control**